
**NOUVEAU - NEU**

Lambda 0.050  
I-I / BKZ E/RF3 cr  
kg / m<sup>3</sup> 230

**STEICO isorel - Panneau standard - dim. 2500 x 1200 mm****STEICO isorel - Standardplatte - Dim. 2500 x 1200 mm**



Art. n° <i>Art. Nr.</i>	Epaisseur <i>Stärke</i>	Spécification <i>Spezifikation</i>	pnx / pal. <i>Platten / Pal.</i>	m <sup>2</sup> /palette <i>m<sup>2</sup>/Palette</i>	Fr./m <sup>2</sup> <i>Fr./m<sup>2</sup></i>
19567	10 mm	bords droits	114	342	2.97
19568	12 mm	<i>rundum stumpfkantig</i>	95	285	3.57
19569	15 mm	bords droits	76	228	4.46
19570	19 mm	<i>rundum stumpfkantig</i>	80	180	5.65

**NOUVEAU - NEU**

Lambda 0.037  
I-I / BKZ E/RF3 cr  
kg / m<sup>3</sup> 110

**STEICO therm dry - Isolant rigide, performant et léger - dim. 1350 x 600 mm****STEICO therm dry - Steife Wärmedämmung, effizient und leicht - Dim. 1350 x 600 mm**

Art. n° <i>Art. Nr.</i>	Epaisseur <i>Stärke</i>	Spécification <i>Spezifikation</i>	Format utile <i>Deckmass</i>	pnx / pal. <i>Platten / Pal.</i>	m <sup>2</sup> /palette <i>m<sup>2</sup>/Palette</i>	Fr./m <sup>2</sup> <i>Fr./m<sup>2</sup></i>
19552	40 mm	bords droits / <i>stumpfkantig</i>		56	45.36	10.14
19553	60 mm	bords droits / <i>stumpfkantig</i>		38	30.78	14.06
19554	80 mm	bords droits / <i>stumpfkantig</i>		28	22.68	18.78
19555	100 mm	bords droits / <i>stumpfkantig</i>		22	17.82	23.44
19556	120 mm	bords droits / <i>stumpfkantig</i>		18	14.58	28.24
19557	140 mm	avec battues / <i>gefälzt</i>	1335 x 585 mm	16	12.96	32.71
19558	160 mm	avec battues / <i>gefälzt</i>	1335 x 585 mm	14	11.34	37.48
19560	120 mm	avec battues / <i>gefälzt</i>	1335 x 585 mm	12	9.72	42.04
19561	180 mm	avec battues / <i>gefälzt</i>	1335 x 585 mm	12	9.72	46.86
19562	200 mm	avec battues / <i>gefälzt</i>	1335 x 585 mm	10	8.10	52.61
19563	240 mm	avec battues / <i>gefälzt</i>	1335 x 585 mm	10	8.10	57.45
19564	260 mm	bords droits / <i>stumpfkantig</i>		8	6.48	62.07
19565	280 mm	bords droits / <i>stumpfkantig</i>		8	6.48	66.85
19566	300 mm	bords droits / <i>stumpfkantig</i>		8	6.48	71.62

**NOUVEAU - NEU**

Lambda 0.036  
I-I / BKZ E/RF3 cr  
kg / m<sup>3</sup> 60

**STEICO flex 036 - Laine isolante flexible - dim. 1220 x 575 mm****STEICO flex 036 - Flexible Dämmwolle - Dim. 1220 x 575 mm**

Art. n° <i>Art. Nr.</i>	Epaisseur <i>Stärke</i>	Spécification <i>Spezifikation</i>	pnx / pal. <i>Platten / Pal.</i>	m <sup>2</sup> /palette <i>m<sup>2</sup>/Palette</i>	Fr./m <sup>2</sup> <i>Fr./m<sup>2</sup></i>
19516	30 mm	bords droits	160	112.24	5.52
19517	40 mm	<i>rundum stumpfkantig</i>	120	84.18	5.58
19518	50 mm	bords droits	90	63.13	6.62
19519	60 mm	<i>rundum stumpfkantig</i>	80	56.12	7.97
19520	80 mm	bords droits	60	42.09	10.37
19521	100 mm	<i>rundum stumpfkantig</i>	48	33.67	12.97
19522	120 mm	bords droits	40	28.06	15.57
19523	140 mm	<i>rundum stumpfkantig</i>	40	28.06	18.16
19524	160 mm	bords droits	30	21.04	20.76
19525	180 mm	<i>rundum stumpfkantig</i>	24	16.83	23.36
19526	200 mm	bords droits	24	16.83	25.94
19527	220 mm	<i>rundum stumpfkantig</i>	20	14.03	29.60
19528	240 mm	bords droits	20	14.03	32.30

